



FIRST PART APPROVAL REQUIRED
 APPROVED BY _____
 DATE _____

Specifications
1 1/2" - 10ga. Standard Duty

- Wire Mesh: 10ga wire. 1 1/2" woven wire mesh, clinched to frames.
- Frames: Vertical members are 1 1/4" x 5/8" roll formed box channels, mortised and tenoned at corner. Holes for 1/4" bolts. Horizontal members are 1" x 1/2" roll formed channels, mortised and tenoned at corner for extra strength.
- Center Reinforcement: Two 1" x 3/8" roll formed channels bolted together through the mesh.
- Top Capping: 2 1/4" x 1" roll formed galvanized channel for 1/4" U-bolts 24" on center.
- Floor Shoes: Cast Iron
- Sweep Space: 2 1/2"
- Hardware: Zinc plated. All necessary interconnecting hardware for installation furnished. Wall and floor anchors optional.
- Finish: Shop coat of Dark Gray PM9017. The paint finish specified is for interior use only. Material must be stored inside in a dry well ventilated area. Do not store outside exposed to the elements.

		TITLE		
		1 1/2" diamond - 10ga mesh 2' x 10'H base panel		
SIZE	COLOR	DWG NO	REV	
B	Dk Gray	300120		
DRAWN	Jesse Pifer	2/21/2024	SCALE 1:13	WEIGHT 32 lbs
			SHEET 1/1	